Amendments to the Claims:

A clean version of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121(c)(3). This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claims 1-4. (Canceled)

5. (Currently amended) A resonant converter comprising: multiple outputs; and

a transformer with a primary winding and at least two secondary windings of different winding directions;

a capacitive element in series with the primary winding;

at least one external inductive element in series with the capacitive element and the primary winding; and

multiple outputs coupled to the secondary windings of the transformer;

wherein the resonant frequency of the resonant converter is determined by the main inductance and the leakage inductances of the transformer, and by a the capacitive element, and the external inductive element.

Claims 6-7. (Canceled)

8. (Previously Presented) A resonant converter, comprising: multiple outputs; and

a transformer with a primary winding and at least two secondary windings of different winding directions,

wherein the secondary windings of the transformer are connected to the converter outputs by way of one diode and one output filter each.

Appl. No. 10/797,791 Amendment and/or Response Reply to Office action of 26 October 2005

9. (Previously Presented) A resonant converter comprising: multiple outputs; and

a transformer with a primary winding and at least two secondary windings of different winding directions,

wherein different ratios of output voltage to number of turns are provided in respect of associated secondary windings having different winding directions.

Claim 10. (Canceled)

11. (Currently Amended) The resonant converter of claim 5-2, further including:

an inverter coupled to the primary winding of the transformer; and means for deriving from each of the multiple outputs a measuring signal for regulating converter an output voltage of the inverter voltages from each multiple output associated with the first group of secondary windings.

- 12. (Previously Presented) The resonant converter of claim 11, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically separated from one another.
- 13. (Previously Presented) The resonant converter of claim 5, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically separated from one another.

Claim 14. (Canceled)

- 15. (Previously Presented) The resonant converter of claim 8, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically separated from one another.
- 16. (Previously Presented) The resonant converter of claim 9, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically separated from one another.
- 17. (Previously Presented) The resonant converter of claim 5, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically connected to one another.
- 18. (Previously Presented) The resonant converter of claim 17, wherein the secondary windings are connected to a ground potential.

Claims 19-20. (Canceled)

21. (Previously Presented) The resonant converter of claim 8, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically connected to one another.

- 22. (Previously Presented) The resonant converter of claim 21, wherein the secondary windings are connected to a ground potential.
- 23. (Previously Presented) The resonant converter of claim 9, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically connected to one another.
- 24. (Previously Presented) The resonant converter of claim 23, wherein the secondary windings are connected to a ground potential.
- 25. (Previously Presented) The resonant converter of claim 11, wherein the transformer has a first group of secondary windings with one or more secondary windings having a first winding direction and a second group of secondary windings with one or more secondary windings having a second winding direction, at least two of the secondary windings being electrically connected to one another.
- 26. (Currently Amended) The resonant converter of claim <u>25-27</u>, wherein the secondary windings are connected to a ground potential.